FLEXA
LIGHTING
NORTH AMERICA

ARIK 6

Ceiling mounted luminaire

IP20 Class 2 **made in Canada**

design Roberto Mantovani

The Arik range of surface-mounted fixtures combines minimal geometry with high mechanical and optical quality. Incredibly easy to install, it is ideal for applications ranging from the accenting of display elements and architectural details to general lighting.

La gamme d'appareils à plafond Arik associe une géométrie minimaliste et une qualité mécanique et optique de haut niveau. Avec une très grande simplicité d'installation, elle se prête à des applications vont de l'éclairage de mise en valeur d'éléments d'exposition ou de détails architectoniques à l'éclairage général.

La gama de aparatos de plafón Arik combina una geometría minimalista con una calidad mecánica y óptica de alto nivel. Gracias a su gran sencillez de instalación, es ideal para aplicaciones que van desde la iluminación puntual para resaltar elementos de exposiciones o detalles arquitectónicos hasta la iluminación general.

Supply current
Courant d'alimentation
Corriente de alimentación
Static White: 500mA (V_f 9V)
Dim To Warm: 250mA (V_f 18V)

Power
Pouissance
Potencia
Static White: 4,5W
Dim To Warm: 4,5W

Series wiring
Câblage en série
Cableado en serie

LED selection
Sélection des LED
Selección del LED
2-Step MacAdam

CRI
98

Lumens

2400K	**406 lm**
2700K	**517 lm**
3000K	**541 lm**
3500K	**548 lm**
4000K	**541 lm**
DW	**358 lm**

Dimensions
Dimensiones



Photometric diagrams
Diagrammes photométriques
Diagramas fotométricos

F002 - 25°



F409 - 45°



Code construction
Construction du code produit
Construcción del código de producto

AW6 X X X X

CC
Remote driver

24	**27**	**30**	**35**	**40**	**DW**
2400K	2700K	3000K	3500K	4000K	Dim to Warm

1	**2**
25°	45°

1	**5**	**C**
White	Black	Custom

Static White 500mA drivers
Static White Alimentateurs 500mA
Static White Alimentadores 500mA

CCPRO10A-500 (1..2) IP20
Dimming: PHASE - 0-10V

CCPRO40A-500 (1..6) IP20
Dimming: PHASE - 0-10V

Dim to Warm 250mA drivers
Dim to Warm Alimentateurs 250mA
Dim to Warm Alimentadores 250mA

CCPRO10A-250-DW (1..2) IP20
Dimming: PHASE - 0-10V

CCPRO40A-250-DW (1..3) IP20
Dimming: PHASE - 0-10V