

GAGA

Wall mounted luminaire

IP20 Class 2  made in Canada

design Lapo Grassellini



Wall mountable, dual emission fixture with extremely simple geometry. Thanks to the directionality of COB LED light sources, the lighting effect is soft and effective.

Appareil mural bi-émission à la géométrie extrêmement simple. En exploitant l'orientation des sources LED COB, l'effet lumineux se révèle particulièrement efficace et doux.

Aparato de pared biemisión de geometría sumamente sencilla. Aprovechando la posibilidad de orientar las fuentes LED COB, el efecto luminoso resulta especialmente eficaz y suave.

Supply current

Courant d'alimentation
Corriente de alimentación
Static White: 500mA (V_i2x18V)
Dim To Warm: 250mA (V_i2x18V)

Power

Pouissance
Potencia
Static White: 2x9W
Dim To Warm: 2x7,2W

Series wiring

Câblage en série
Cableado en serie

LED selection

Sélection des LED
Selección del LED
2-Step MacAdam

CRI


98

Lumens

2400K	1456 lm
2700K	2128 lm
3000K	2232 lm
3500K	1260 lm
4000K	2228 lm
DW	1260 lm

Dimensions

Dimensiones



Code construction

Construction du code produit
Construcción del código de producto

GG1 X X 9

24	27	30	35	40	DW
2400K	2700K	3000K	3500K	4000K	Dim to Warm
1	5	C			
White	Black	Custom			

Static White 500mA drivers

Static White Alimentateurs 500mA

Static White Alimentadores 500mA

CCPRO40A-500 (1) IP20

Dimming: PHASE - 0-10V

Dim to Warm 400mA drivers

Dim to Warm Alimentateurs 400mA

Dim to Warm Alimentadores 400mA

CCPRO40A-400 (1) IP20

Dimming: PHASE - 0-10V

Tunable White 500mA drivers

Tunable White Alimentateurs 500mA

Tunable White Alimentadores 500mA

DL0561S1 (1) IP20

Dimming: 0-10V