

ZERINO

Trimless downlight

design Roberto Mantovani

The trimless Zerino range combines minimal dimensions with a wide range of optics and the viewing comfort offered by recessed optics. Attention to mechanical and optical performance guarantees the highest quality product for the creation of starry skies or subtle light accents.

La gamme trimless Zerino combine les dimensions minimales à la possibilité de choisir différentes optiques et au confort visuel proposé par l'optique en retrait. Le soin des mécaniques et l'attention pour les prestations optiques garantissent un produit de haute qualité pour la réalisation de ciels étoilés ou de petits accents lumineux.

La gama trimless Zerino combina el tamaño mínimo con la posibilidad de elegir diferentes ópticas y con un confort visual gracias a su óptica retrocedida. La atención por las partes mecánicas y por las prestaciones ópticas garantizan un producto de alta calidad para la realización de cielos estrellados o de pequeños puntos luminosos.



IP20 Class 2  made in Canada

Supply current

Courant d'alimentation
Corriente de alimentación
250mA (V_i 2,9V)

Power

Puissance
Potencia
0,75W

Series wiring

Câblage en série
Cableado en serie

LED selection

Sélection des LED
Selección del LED
3-Step MacAdam

CRI


90

Lumens

	250mA
2700K	81 lm
3000K	81 lm
3500K	100 lm
4000K	107 lm

Dimensions


Dimensiones



Photometric diagrams

Diagrammes photométriques

Diagramas fotométricos




Code construction

Construction du code produit

Construcción del código de producto

ZK1 X X X



Accessories

Accessoires


Accesorios

AT064R01030

Airtight recessed housing for insulated ceiling

IC064R01030

Recessed housing for insulated ceiling




MP-R030

Baseplate




R01030

T-bar baseplate



ZQC00K White

Plasterboard recessing frame




ZQC00K.BMK-WH White

ZQC00K.BMK-BLK Black

ZQC00K.BMK-CU Custom

Backmount frame for hard surfaces



250mA drivers

Alimentateurs 250mA

Alimentadores 250mA

CCPRO10A-250 (1..12) IP20

Dimming: PHASE - 0-10V

CCPRO40A-250 (1..18) IP20

Dimming: PHASE - 0-10V