



# BLACK 6


design: Lapo Grassellini

**Supply current**  
 Courant d'alimentation  
 Corriente de alimentación  
**500mA (V<sub>f</sub> 8.7V)**

**Power**  
 Pouissance  
 Potencia  
**4.5W**



## Photometric diagrams



CCT	Flux	CRI
2700K	421 lm	98+
3000K	446 lm	98+

## Code Construction


Construction du code produit  
 Construcción del código de producto

**BK2 | X | XX | X | E |**

<b>BK2</b>	<b>X</b>	<b>Finishing</b> Finitions Acabados	<b>XX</b>	<b>Color Temp.</b> Température couleur Temperatura de color	<b>X</b>	<b>Beam angle</b> Angle de faisceau Ángulo del haz
		<b>1</b> White Blanc Blanco		<b>27</b> 2700K		<b>S</b> 25°
		<b>2</b> Grey Gris		<b>30</b> 3000K		<b>M</b> 45°
		<b>5</b> Black Noir Negro				

**Drivers (Remote Located)**  
 Alimentateurs  
 Alimentadores

**Series wiring**  
 Câblage en série  
 Cableado en serie



0-10V

**FLEXA-60-PRO-CC-10V**  
 Programmable 60W CC 0-10V Dimming  
 Dimming Range: 0.1%  
 Min. 1/Max. 6 Fixtures per Driver

## IC Housings

**IC064R01045**  
 Recessed Box for  
 Insulated Ceiling with  
 45mm Hole

**AT064R01045**  
 Air Tight Recessed Box  
 for Insulated Ceiling with  
 45mm Hole

