


DAGO 6

design: Roberto Mantovani

Supply current
Courant d'alimentation
Corriente de alimentación


Power
Pouissance
Potencia

500mA (V_i 8.7V) **4.5W**




40x60 mm
(1.57"x2.36")

Photometric diagrams



CCT	Flux	CRI	CCT	Flux	CRI
2400K	472 lm	95+	Dim to Warm 1800K-3000K	416 lm	90
2700K	421 lm	98+			
3000K	446 lm	98+			
3500K	464 lm	98+			
4000K	482 lm	98+			



Code Construction

Construction du code produit
Construcción del código de producto

DG6 | X | 2 | XX | E |


DG6	X	Finishing Finitions Acabados	2	XX	Color Temp. Température couleur Temperatura de color	E
		1 White Blanc Blanco			24 2400K	
		5 Black Noir Negro			27 2700K	
		C Custom Personnalisée Personalizado			30 3000K	
					35 3500K	
					40 4000K	
					DW Dim Warm	
					CU Custom Personnalisée Personalizado	

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie




For other driver options -
including Lutron, Dali and DMX -
please consult factory

Static White	Phase / 0-10V (Dual Dimming)	
500mA	CCPRO10-A Min. 1 Max. 2	CCPRO40-A Min. 1 Max. 6
Dim to Warm	Phase / 0-10V (Dual Dimming)	
250mA	CCPRO10-A Min. 1 Max. 2	CCPRO40-A Min. 1 Max. 3

Optionals - Accessoires - Accesorios

CS1007

Recessing box
Boîtier d'encastrement
Caja de empotrar



Optionals - Accessoires - Accesorios

DCVI.B.1

24VDC Constant Voltage to
Constant Current Converter
0-10V / Phase / Dim to Warm
Compatible, 13W

