


KIRSTEN


design: Lapo Grassellini

Supply current
 Courant d'alimentation
 Corriente de alimentación
350mA (V_f 14V)

Power
 Pouissance
 Potencia
5W



Photometric diagrams



CCT	Flux	CRI
3000K	360 lm	93
4000K	385 lm	93



Code Construction


Construction du code produit
 Construcción del código de producto

KR1 | XX | X₁


KR1	XX	Color Temp. Température couleur Temperatura de color	X	Finishing Finitions Acabados	
	30	3000K	B	White Blanc Blanco	
	40	4000K		G	Grey Gris
	CU	Custom			N
			K	COR-TEN	

Optionals - Accessoires - Accesorios

FXC503 (Indoor)
Recessing box
 Boîtier d'encastrement
 Caja de empotrar



FXC503-OUT (Outdoor)
Recessing box
 Boîtier d'encastrement
 Caja de empotrar




Drivers

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



0-10V

FLEXA-60-PRO-CC-10V
 Programmable 60W CC 0-10V Dimming
 Dimming Range: 0.1%
Min. 1/Max. 3 Fixtures per Driver

Phase

FLEXA-12-350-CC-ELV
 12W 350mA Constant Current
 Dimming Range: 10%
Min. 1/Max. 2 Fixtures per Driver

FLEXA-16-350-CC-ELV
 16W 350mA Constant Current
 Dimming Range: 10%
Min. 2/Max. 3 Fixtures per Driver

Lutron 2-Wire Phase

LTEA.1
 Hi-Lume 2-Wire Phase
 350mA Constant Current
 Dimming Range: 1%
Min. 1/Max. 1 Fixtures per Driver

LTEA.2
 Hi-Lume 2-Wire Phase
 350mA Constant Current
 Dimming Range: 1%
Min. 2/Max. 2 Fixtures per Driver

Lutron Ecosystem

LDE.1
 Hi-Lume Ecosystem
 350mA Constant Current
 Dimming Range: 1%
Min. 1/Max. 1 Fixtures per Driver

LDE.2
 Hi-Lume Ecosystem Premier
 350mA Constant Current
 Dimming Range: 1%
Min. 3/Max. 3 Fixtures per Driver