


MILO X130


design: Lapo Grassellini

Supply current
Courant d'alimentation
Corriente de alimentación
500mA (V_f 3 x 18V)

Power
Puissance
Potencia
3 x 10W



Photometric diagrams



CCT	Flux _(x3)	CRI
2400K	837 lm	95+
2700K	921 lm	98+
3000K	977 lm	98+
3500K	1016 lm	98+
4000K	1055 lm	98+

CCT	Flux	CRI
Dim to Warm 1800K-3000K	725 lm	95
Tunable White 2700K-5000K	952 lm	95

Code Construction

Construction du code produit
Construcción del código de producto

MLX13 | X | XX | 9 | X |


MLX13	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	9	X	Beam angle Angle de faisceau Ángulo del haz
		1 White Blanc Blanco		24 2400K			S 36°
		5 Black Noir Negro		27 2700K			M 46°
		C Custom Personnalisée Personalizado		30 3000K			W 60°
				35 3500K			D 20+55° (Elliptical)
				40 4000K			
				DW Dim Warm			
				TW Tunable White			
				CU Custom Personnalisée Personalizado			

Drivers (Remote)


Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie



For other driver options -
including Lutron, Dali and DMX -
please consult factory



3 x L001


Low luminance louvre
Filtre basse luminance
Filtro de baja luminancia



Note: the filter must be ordered together with the lighting fixture
Note: le filtre doit être commandé en même temps que l'appareil
Note: el filtro debe pedirse junto con la luminaria

MP-X211


Mounting Plate
with 211x77mm Hole



T-Bar Installation

X03211

Mounting Plate
with 211x77mm Hole




IC Housings

IC127X03211

Recessed Box for
Insulated Ceiling
with 211x77mm Hole

AT127X03211

Air Tight Recessed
Box for Insulated
Ceiling with
211x77mm Hole




Accessories - Accessoires - Accesorios

MLX13Q

Plasterboard recessing frame

Boîtier d'encastrement
pour plaques de plâtre
Cajetín para placas de yeso




Hole Cut:
77mm x 211mm
(3.03" x 8.31")

MLX13Q.WF

Backmount frame

Pierre/bois montage arrière
Roca/madera montaje trasero



Hole Cut:
74mm x 207mm
(2.91" x 8.15")

Optionals - Accessoires - Accesorios

3 x DCVI.B.1

24VDC Constant Voltage to
Constant Current Converter
0-10V / Phase / Dim to Warm
Compatible, 13W

