


# MINE 6

design: Lapo Grassellini




**Supply current**  
 Courant d'alimentation  
 Corriente de alimentación  
**500mA** (V<sub>f</sub> 8.7V)

**Power**  
 Pouissance  
 Potencia  
**4.5W**



## Photometric diagrams



CCT	Flux	CRI
2700K	128 lm	98+
3000K	133 lm	98+
3500K	142 lm	98+
4000K	154 lm	85
Custom	TBD	

## Code Construction

Construction du code produit  
 Construcción del código de producto

**MN6 | X | XX | X | E |**


MN6	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	X	Beam angle Angle de faisceau Ángulo del haz	E
	1	White Blanc Blanco	27	2700K	S	25°	
	2	Grey Gris	30	3000K	M	60°	
	5	Black Noir Negro	35	3500K			
			40	4000K			
			CU	Custom			

## Drivers

Alimentateurs  
 Alimentadores

## Series wiring

Câblage en série  
 Cableado en serie



0-10V

## FLEXA-60-PRO-CC-10V

Programmable 60W CC 0-10V Dimming  
 Dimming Range: 0.01%  
**Min 1./Max. 6 Fixtures per Driver**

Phase

## FLEXA-12-500-CC-ELV

12W 500mA Constant Current  
 Dimming Range: 10%  
**Min. 1/Max. 2 Fixtures per Driver**

## FLEXA-23-500-CC-ELV

23W 500mA Constant Current  
 Dimming Range: 10%  
**Min 3./Max. 5 Fixtures per Driver**

## Lutron Forward Phase

### LTEA.1

Hi-Lume Forward Phase  
 20W 500mA Constant Current  
 Dimming Range: 1%  
**Min. 2/Max. 4 Fixtures per Driver**

### LTEA.2

Hi-Lume Forward Phase  
 30W 500mA Constant Current  
 Dimming Range: 1%  
**Min. 4/Max. 6 Fixtures per Driver**


## Lutron Ecosystem

### PEQ.1

Hi-Lume ECO System  
 20W 500mA Constant Current  
 Dimming Range: 1%  
**Min. 2/Max. 4 Fixtures per Driver**


### PEQ.0

Hi-Lume ECO System Premier  
 20W 500mA Constant Current  
 Dimming Range: 0.1%  
**Min. 2/Max. 4 Fixtures per Driver**




**R01050-WOA**  
 Mounting Plate  
 with 50mm Hole

A - 152.4mm (6")  
 B - 152.4mm (6")  
 C - 50mm (1.97")



**R01050**  
 Mounting Plate  
 with 50mm Hole

A - 152.4mm (6")  
 B - 152.4mm (6")  
 C - 50mm (1.97")



**IC064R01050**  
 Recessed Box for Insulated Ceiling  
 with 50mm Hole

**AT064R01050**  
 Air Tight Recessed Box for Insulated  
 Ceiling with 50mm Hole