


# MINILED A QX120


design: Lapo Grassellini

**Supply current**  
 Courant d'alimentation  
 Corriente de alimentación  
**350mA (V<sub>f</sub> 2 x 8.7V)**

**Power**  
 Pouissance  
 Potencia  
**2 x 3W**



### Photometric diagrams



CCT	Flux (lx)	CRI
2700K	128 lm	98+
3000K	133 lm	98+
3500K	142 lm	98+
4000K	154 lm	85
Custom	TBD	

### Code Construction

Construction du code produit  
 Construcción del código de producto

**MLDQX12 | X | XX | X | E**


<b>MLDQX12</b>	<b>X</b>	<b>Finishing</b> Finitions Acabados	<b>XX</b>	<b>Color Temp.</b> Température couleur Temperatura de color	<b>X</b>	<b>Beam angle</b> Angle de faisceau Ángulo del haz	<b>E</b>
		<p><b>1</b> White Blanc Blanco</p> <p><b>2</b> Grey Gris</p> <p><b>5</b> Black Noir Negro</p>		<p><b>27</b> 2700K</p> <p><b>30</b> 3000K</p> <p><b>35</b> 3500K</p> <p><b>40</b> 4000K</p> <p><b>CU</b> Custom</p>		<p><b>S</b> 25°</p> <p><b>M</b> 60°</p>	

### Drivers

Alimentateurs  
 Alimentadores

### Series wiring

Câblage en série  
 Cableado en serie



### 0-10V

**FLEXA-60-PRO-CC-10V**  
 Programmable 60W CC 0-10V Dimming  
 Dimming Range: 0.01%  
**Min 1./Max. 3 Fixtures per Driver**

### Phase

**FLEXA-12-350-CC-ELV**  
 12W 350mA Constant Current  
 Dimming Range: 10%  
**Min. 1/Max. 1 Fixtures per Driver**

**FLEXA-16-350-CC-ELV**  
 16W 350mA Constant Current  
 Dimming Range: 10%  
**Min 2./Max. 2 Fixtures per Driver**

### Lutron Forward Phase


**LTEA.1**  
 Hi-Lume Forward Phase  
 20W 350mA Constant Current  
 Dimming Range: 1%  
**Min. 1/Max. 2 Fixtures per Driver**

**LTEA.2**  
 Hi-Lume Forward Phase  
 30W 350mA Constant Current  
 Dimming Range: 1%  
**Min. 2/Max. 3 Fixtures per Driver**

### Lutron Ecosystem


**PEQ.1**  
 Hi-Lume ECO System  
 20W 350mA Constant Current  
 Dimming Range: 1%  
**Min. 1/Max. 2 Fixtures per Driver**

**PEQ.0**  
 Hi-Lume ECO System Premier  
 20W 350mA Constant Current  
 Dimming Range: 0.1%  
**Min. 1/Max. 2 Fixtures per Driver**




**X02105-WOA**  
 Mounting Plate  
 with 105x58mm Hole

A - 203.2mm (8")  
 B - 203.2mm (8")  
 C - 105mm (4.13")  
 x 58mm (2.28")



**X02105**  
 Mounting Plate  
 with 105x58mm Hole

A - 203.2mm (8")  
 B - 203.2mm (8")  
 C - 105mm (4.13")  
 x 58mm (2.28")



**IC086X02105**  
 Recessed Box for Insulated Ceiling  
 with 105x58mm Hole

**AT086X02105**  
 Air Tight Recessed Box for Insulated  
 Ceiling with 105x58mm Hole