


MINISASHA 110 U

design: Lapo Grassellini




Supply current
 Courant d'alimentation
 Corriente de alimentación
350mA (V_f 8.7V)

Power
 Pouissance
 Potencia
3W



Photometric diagrams



CCT	Flux	CRI
2700K	267 lm	93
3000K	279 lm	93
3500K	292 lm	93
4200K	309 lm	93



Code Construction

Construction du code produit
 Construcción del código de producto


MSU11 | X | X | XX |

MSU11	X	Finishing Finitions Acabados	X	Beam angle Angle de faisceau Ángulo del haz	XX	Color Temp. Température couleur Temperatura de color
	1	White Blanc Blanco	1	18°	27	2700K
	5	Black Noir Negro	2	40°	30	3000K
	C	Custom Personnalisée Personalizado			35	3500K
					42	4200K
					CU	Custom Personnalisée Personalizado

Drivers (Remote)

Alimentateurs
 Alimentadores

Series wiring
 Câblage en série
 Cableado en serie



For other driver options -
 including Lutron, Dali and DMX -
 please consult factory

Static White	Phase / 0-10V (Dual Dimming)	
350mA	CCPRO10-A Min. 1 Max. 3	CCPRO40-A Min. 1 Max. 6

DCVI.B.1

24VDC Constant Voltage to
 Constant Current Converter
 0-10V / Phase / Dim to Warm
 Compatible, 13W

