


PUFF


design: Lapo Grassellini

Supply current
 Courant d'alimentation
 Corriente de alimentación
250mA (V_I 8.7V)

Power
 Pouissance
 Potencia
2W



Photometric diagrams



CCT	Flux	CRI
2700K	178 lm	93
3000K	186 lm	93
3500K	194 lm	93
4200K	206 lm	93



Code Construction

Construction du code produit
 Construcción del código de producto

PU_|X_|X_|XX_|X_|


PU	X	Finishing Finitions Acabados	X	Beam angle Angle de faisceau Ángulo del haz	XX	Color Temp. Température couleur Temperatura de color	X	Low luminace louvre Filtre basse luminace Filtro de baja luminancia
	1	White Blanc Blanco	1	18°	27	2700K	L	Yes Oui Si
	2	Grey Gris	2	40°	30	3000K	0	No Non
	5	Black Noir Negro			35	3500K		
					42	4200K		
					CU	Custom		

Drivers

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



Lutron 2-Wire Phase

LTEA.1
 Hi-Lume 2-Wire Phase
 250mA Constant Current
 Dimming Range: 1%
Min. 1/Max. 2 Fixtures per Driver

LTEA.3
 Hi-Lume 2-Wire Phase
 250mA Constant Current
 Dimming Range: 1%
Min. 3/Max. 6 Fixtures per Driver

0-10V

FLEXA-60-PRO-CC-10V

Programmable 60W CC 0-10V Dimming

Dimming Range: 0.1%

Min. 1/Max. 6 Fixtures per Driver