


SIGN

design: Lapo Grassellini




Supply current
 Courant d'alimentation
 Corriente de alimentación
350mA (V_f 15V)

Power
 Pouissance
 Potencia
5W



Photometric diagrams



CCT	Flux	CRI
3000K	360 lm	93
4000K	385 lm	93

Code Construction

Construction du code produit
 Construcción del código de producto

SG1 | XX X |


SG1	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color
		B White Blanc Blanco		30 3000K
		G Grey Gris		40 4000K
		N Black Noir Negro		CU Custom
		K COR-TEN		

Drivers

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



0-10V

FLEXA-60-PRO-CC-10V

Programmable 60W CC 0-10V Dimming

Dimming Range: 0.1%

Min. 1/Max. 3 Fixtures per Driver

Phase

FLEXA-12-350-CC-ELV

12W 350mA Constant Current

Dimming Range: 10%

Min. 1/Max. 2 Fixtures per Driver

FLEXA-16-350-CC-ELV

16W 350mA Constant Current

Dimming Range: 10%

Min. 2/Max. 3 Fixtures per Driver

Lutron 2-Wire Phase

LTEA.1

Hi-Lume 2-Wire Phase

350mA Constant Current

Dimming Range: 1%

Min. 1/Max. 1 Fixtures per Driver

LTEA.3

Hi-Lume 2-Wire Phase

350mA Constant Current

Dimming Range: 1%

Min. 2/Max. 3 Fixtures per Driver

Lutron Ecosystem

LDE.1

Hi-Lume Ecosystem

350mA Constant Current

Dimming Range: 1%

Min. 1/Max. 1 Fixtures per Driver

LDE.2

Hi-Lume Ecosystem Premier

350mA Constant Current

Dimming Range: 1%

Min. 2/Max. 3 Fixtures per Driver