


# TASK 10


design: Roberto Mantovani

**Supply current**  
 Courant d'alimentation  
 Corriente de alimentación  
**500mA (V<sub>I</sub> 18V)**

**Power**  
 Pouissance  
 Potencia  
**10W**



## Photometric diagrams



CCT	Flux	CRI
2700K	921 lm	98+
3000K	977 lm	98+
3500K	1016 lm	98+
4000K	1055 lm	98+
† Dim Warm 1800K-3000K	725 lm	95

## Code Construction

Construction du code produit  
 Construcción del código de producto

**TW | X | XX | 9 | 1**


TW	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	9	1	Beam angle Angle de faisceau Ángulo del haz
		<b>1</b> White Blanc Blanco		<b>27</b> 2700K			<b>1</b> 10°
		<b>2</b> Grey Gris		<b>30</b> 3000K			
		<b>5</b> Black Noir Negro		<b>35</b> 3500K			
				<b>40</b> 4000K			
				<b>DW</b> Dim Warm † @ 420mA			

## Drivers

Alimentateurs  
 Alimentadores

## Series wiring

Câblage en série  
 Cableado en serie



0-10V

### FLEXA-60-PRO-CC-10V

Programmable 60W CC 0-10V Dimming  
 Dimming Range: 0.1%  
**Min. 1/Max. 3 Fixtures per Driver**

Phase

### FLEXA-12-500-CC-ELV

12W 500mA Constant Current  
 Dimming Range: 10%  
**Min. 1/Max. 1 Fixtures per Driver**

### FLEXA-23-500-CC-ELV

23W 500mA Constant Current  
 Dimming Range: 10%  
**Min. 2/Max. 2 Fixtures per Driver**

Lutron 2-Wire Phase

### LTEA.2

Hi-Lume 2-Wire Phase  
 500mA Constant Current  
 Dimming Range: 1%  
**Min. 1/Max. 2 Fixtures per Driver**

### LTEA.3

Hi-Lume 2-Wire Phase  
 500mA Constant Current  
 Dimming Range: 1%  
**Min. 2/Max. 3 Fixtures per Driver**

Lutron Ecosystem

### LDE.1


Hi-Lume Ecosystem  
 500mA Constant Current  
 Dimming Range: 1%  
**Min. 1/Max. 1 Fixtures per Driver**

### LDE.2

Hi-Lume Ecosystem Premier  
 500mA Constant Current  
 Dimming Range: 1%  
**Min. 2/Max. 2 Fixtures per Driver**

## MP-R060


Mounting Plate  
 with 60mm Hole



## T-BAR Installation

### RO1060

Mounting Plate  
 with 60mm Hole



## IC Housings

### IC064R01060

Recessed Box for  
 Insulated Ceiling with  
 60mm Hole

### AT064R01060

Air Tight Recessed Box  
 for Insulated Ceiling with  
 60mm Hole

