


ZOOM

design: Lapo Grassellini



Supply current
Courant d'alimentation
Corriente de alimentación
500mA (V_f 2.9V)

Power
Pouissance
Potencia
1.5W



Adjustable optics

Optique réglable
Óptica ajustable

10-55°

CCT	Flux	CRI
2700K	128 lm	93
3000K	133 lm	93
3500K	143 lm	93
4000K	154 lm	93

Code Construction

Construction du code produit
Construcción del código de producto

ZM1 | X | XX |


ZM1	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	Adjustable optics Optique réglable Óptica ajustable
		2 Aluminum Aluminium Aluminio		27 2700K	10-55°
		5 Black Noir Negro		30 3000K	
		6 Bronze Bronce		35 3500K	
		C Custom Personnalisée Personalizado		40 4000K	
				CU Custom Personnalisée Personalizado	

Drivers (Remote)

Alimentateurs
Alimentadores

Series wiring

Câblage en série
Cableado en serie



For other driver options - including Lutron, Dali and DMX - please consult factory


Static White	Phase / 0-10V (Dual Dimming)	
500mA	CCPR010-A Min. 1 Max. 6	CCPR040-A Min. 1 Max. 18

Note: cable cut to measure on request
Note: câble sur mesure disponible sur demande
Nota: cable a medida disponible a petición

Optionals - Accessoires - Accesorios

XP0011

Earth spike
Piquet de terre
Pico de la tierra



XP0200

Aluminum
Aluminium
Aluminio

XP0500

Black
Noir
Negro

XP0600

Bronze
Bronce

Base

